## **Forklift Seat Belt**

Seat Belt for Forklifts - This guideline purpose is to be able to describe the Regulation requirements for the application of driver seatbelts or restraints on lift trucks. It is the employers' accountability to make certain that each and every machine, piece of equipment and tool inside the workplace is chosen and utilized properly and worked according to the manufacturer's instructions.

Rough Terrain forklifts ought to meet the guidelines of ANSI Standard ASME B56.6-1992 with regards to their use, design, maintenance, inspection and fabrication.

Side boom tractors and mobile equipment together with a Rollover Protective Structure, or ROPS for short, must have seat belts that satisfy the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If any mobile machine includes seat belts required by law, the operator and subsequent passengers must ensure they use the belts whenever the vehicle is in motion or engaged in operation in view of the fact that this can cause the equipment to become unstable and hence, not safe.

If a seat belt or different operator restraint is required on a forklift.

The seat belt requirements while operating a lift truck depend on various factors. Whether or not the lift truck is equipped along with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was actually manufactured all add to this determination. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to a driver restraint device, system or enclosure, ANSI Standard ASME B56.1-1993 in the case of powered industrial trucks, is designed to help the driver in reducing the possibility of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The restraint device or system may comprise a seat belt, though a seat belt is not essentially a part of such device or system.